



Number: UKCA/0558/22/032 Replaces: 18GR0200/01

Issue Date: 07-02-2022 Contract Number: PS7169

Due Date: 07-02-2032 Module: B (Type Testing)

Report Number: 120052 Scope: Gas Appliances

PIN: 0063AU1052 **Page** 1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

VE4..AA

Manufactured by Honeywell Product and Solutions Sarl

Rolle, Switzerland

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: BS EN 161:2011+A3:2013

Signed on behalf of Kiwa Ltd. (UK Approved Body Number 0558)

m 1 Contre

Mark Crowther Technical Director

Kiwa Ltd.

Kiwa Gastec

Malvern View Business Park Stella Way Bishops Cleeve Cheltenham GL52 7DQ United Kingdom

T +44 (0)1242 677877 **F** +44 (0)1242 676506

www.kiwa.co.uk





0217



Number: UKCA/0558/22/032 Replaces: 18GR0200/01

Issue Date: 07-02-2022 Contract Number: PS7169

Due Date: 07-02-2032 Module: B (Type Testing)

Report Number: 120052 Scope: Gas Appliances

PIN: 0063AU1052 **Page** 2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

The Honeywell Technologies Sarl automatic shut-off valve(s), Series VE4..AA, are intended for use on gas burners, gas appliances and similar use.

List of all available types:

VE4..AA

Automatic shut-off valve approved on EN161

Class : A Mechanical group : 2

Supply Voltage (Rp 3/8" .. 3/4") : 230Vac / 50Hz

: 110Vac / 50Hz

Supply voltage (Rp 1/4") : 230 Vrac / 50Hz

: 110 Vrac / 50Hz

Degree of protection : IP65

Max. ambient temperature : -150C / 600C

Max. inlet pressure : 500mbar for Rp1/4"

: 200mbar for Rp3/8" to Rp3/4"

Type survey:

VE...AA : shut-off valve : line voltage

... 08..
... 10..
... 15..
... 20..
: connection Rp3/8 (aluminum body)
: connection Rp1/2 (aluminum body)
: connection Rp3/4 (aluminum body)