

Index protective cap

for diaphragm gas meters
with roller type index



Applications

The protective cap protects the index against the ingress of water and dirt. Diaphragm meters with mounted cap are suitable for use in flood risk areas.

Brief information

The transparent protective cap is mounted on the index and sealed with the housing. A packet of desiccant prevents condensation and with it the steaming up of the index window.

Advice: The calibration seal is located under the protective cap and only accessible after its dismantling. The pulse output is not usable in conjunction with the protective cap.

Main features

- Protection class IP 67
- Suitable for BK-G2.5 – BK-G25

Your contacts

Germany
Elster GmbH
Steinern Str. 19 - 21
55252 Mainz-Kastel
T +49 6134 605 0
F +49 6134 605 223
www.elster-instromet.com
info@elster-instromet.com

Belgium
Elster NV/SA
Rijkmakerlaan 9
2910 Essen
T +32 3 670 0700
F +32 3 667 6940
www.elster-instromet.com
info@elster-instromet.com

Singapore
Elster-Instromet Sdn. Bhd. (Singapore Branch)
160 Paya Lebar Road
#04-01 Orion@Paya Lebar
Singapore 409022
T +65 6247 7728
F +65 6247 7729
sales@elster-instromet.com.sg

BGZZwSchKa EN01
A29.01.2010

Subject to change without prior notice
All rights reserved

73030018

