

Eclipse ThermJet Burners

Model TJ0015

Data sheet Edition 9.14

Version 2

Parameter	Burner Velocity		Model TJ0015
Maximum Input, Btu/h (kW)¹	Medium & High Velocity		150,000 (40)
Minimum Input, Btu/h (kW)¹ <i>For lower inputs, contact Eclipse, Inc.</i>	Medium & High Velocity		15,000 (4)
Minimum Input Fixed Air, Btu/h (kW)¹	Medium & High Velocity		3,750 (1)
Main Gas Inlet Pressure, "w.c. (mbar) <i>Fuel pressure at gas inlet Tap B (see page 3)</i>	High Velocity	Natural Gas	13.0 (32.4)
		Propane	15.0 (37.4)
		Butane	15.0 (37.4)
	Medium Velocity	Natural Gas	7.5 (18.7)
		Propane	7.5 (18.7)
		Butane	7.5 (18.7)
Air Inlet Pressure, "w.c. (mbar) <i>15% excess air at maximum input Tap A (see page 3)</i>	High Velocity	Natural Gas	17.0 (42.3)
		Propane	18.0 (44.8)
		Butane	18.0 (44.8)
	Medium Velocity	Natural Gas	11.0 (27.4)
		Propane	11.0 (27.4)
		Butane	11.0 (27.4)
High Fire Visible Flame Length, inches (mm) <i>Measured from the outlet end of the combustor</i>	High Velocity	Natural Gas	9.0 (229)
		Propane	9.0 (229)
		Butane	9.0 (229)
	Medium Velocity	Natural Gas	11.0 (279)
		Propane	10.0 (254)
		Butane	11.0 (279)
Approximate Flame Velocity, ft/s (m/s) <i>Approximately 15% excess air at maximum input</i>	High Velocity		440 (134)
	Medium Velocity		270 (82)
Maximum Combustion Air Temperature	300°F (149°C). For higher temperatures use TJPCA (Datasheet 206).		
Flame Detection	Flame rods can be used with all combustors, any fuel listed below, and operating temperatures up to 2,200°F (1,204°C). UV scanners can be used with all combustors, any fuel listed below, and up to the maximum operating temperature.		
Fuels² <i>For any other mixed gas, contact Eclipse, Inc.</i>	Natural gas, Propane or Butane		
Approvals	 AM30		

1. All imperial inputs based upon gross calorific values (HHV). All metric inputs based upon net calorific values (LHV).



2. See Design Guide 205 for more information about typical fuel composition and properties.

- All information is based on laboratory testing in neutral (0 "w.c., 0 mbar) pressure chamber. Different chamber conditions may affect the data.
- All information is based on standard combustor design. Changes in combustor will alter performance and pressures.
- All inputs based upon standard conditions; 1 atmosphere, 70°F (21°C).
- Eclipse reserves the right to change the construction and/or configuration of our products at any time without being obliged to adjust earlier supplies accordingly.
- Plumbing of air and gas will affect accuracy of orifice readings. All information is based on generally acceptable air and gas piping practices.



elster
Thermal Solutions

Performance Graphs





Emissions correction factor for medium velocity combustor is 1.20. Emissions data based on, on-ratio control firing at 15% excess air corrected to 3% O₂.

Emissions from the burner are influenced by:

- Fuel type
- Combustion air temperature
- Firing rate
- Chamber conditions
- Percent of excess air


For estimates of other emissions, contact Eclipse.



Dimensions and Specifications


Dimensions in mm (inches)

Burner Housing



Burner weight less combustor: 17.9 lbs (8.1 kg)


Tap Locations



Dimensions and Specifications

Dimensions in mm (inches)

Combustors



Dimension	High Velocity	Medium Velocity
ØA	Ø28.4 (1.1)	Ø35.4 (1.4)
B	230.8 (9.1)	223.3 (8.8)
ØC	Ø35 (1.4)	Ø42 (1.7)