Datasheet 206-10
9/20/2014

Eclipse ThermJet Burners for Preheated Combustion Air

Model TJPCA0750

Version 2

Parameter			Specifications		
			Natural Gas	Propane	Butane
Maximum Input, Btu/h (kW)[1]			7,500,000 (1978)	7,500,000 (1978)	7,500,000 (1978)
Minimum Input, Btu/h (kW)[1]			750,000 (198)	750,000 (198)	750,000 (198)
Main Gas Inlet Pressure, "w.c. (mbar) *Fuel pressure at gas inlet* *Tap B (see page 3)*	**Combustion Air Temp**	**Ambient**	6.7 (16.6)	6.7 (16.6)	6.7 (16.6)
		300°F (150°C)	9.3 (23.0)	9.3 (23.0)	9.3 (23.0)
		700°F (370°C)	13.9 (34.6)	13.9 (34.6)	13.9 (34.6)
Air Inlet Pressure, "w.c. (mbar) *15% excess air at maximum input*		**Ambient**	6.3 (15.7)	6.3 (15.7)	6.3 (15.7)
		300°F (150°C)	8.9 (22.2)	8.9 (22.2)	8.9 (22.2)
		700°F (370°C)	13.5 (33.6)	13.5 (33.6)	13.5 (33.6)
Maximum Preheated Air Temperature			700°F (370°C)		
High Fire Visible Flame Length, inches (mm) *Measured from the outlet end of combustor*			<125.0 (3175)	<125.0 (3175)	<130.0 (3302)
Flame Detection			UV scanner available for all combustors.		
Fuels[2] *For any other mixed gas, contact Eclipse for orifice sizing.*			Natural gas, Propane, or Butane		
Approvals			АИ30		


NOT UP-TO-DATE
www.docuthek.com


1. All imperial inputs based upon gross calorific values (HHV). All metric inputs based upon net calorific values (LHV).
2. See Design Guide 205 for more information about typical fuel composition and properties.

- All information is based on laboratory testing in neutral (0 "w.c., 0 mbar) pressure chamber. Different chamber conditions may affect the data.
- All information is based on standard combustor design. Changes in combustor will alter performance and pressures.
- All inputs based upon standard conditions; 1 atmosphere, 70°F (21°C).
- Eclipse reserves the right to change the construction and/or configuration of our products at any time without being obliged to adjust earlier supplies accordingly.
- Plumbing of air and gas will affect accuracy of orifice readings. All information is based on generally acceptable air and gas piping practices.

ECLIPSE®
Innovative Thermal Solutions

Performance Graphs







NOT UP-TO-DATE
www.docuthek.com

Dimensions and Specifications

Dimensions in mm (inches)


Burner Housing






Burner weight less combustor: 133 lbs (60 kg)

Tap Locations







NOT UP-TO-DATE
www.docuthek.com

Dimensions and Specifications
Dimensions in mm (inches)


Combustors







Alloy Combustor (AISI 310)
Weight: 21 lbs (9.5 kg)
Maximum Chamber Temp: 1,750°F (950°C)


[Not Suitable for Preheated Air Over 700°F (371°C)]





Refractory Combustor with AISI 330 wrapper
Weight: 330 lbs (150 kg)
Maximum Chamber Temp: 2,800°F (1,538°C)





Down Firing Block with AISI 330 wrapper
Weight: 310 lbs (140.6 kg)
Maximum Chamber Temp: 2,800°F (1,538°C)

NOTE: Mounting gasket shown on right side of combustor flange. Dimensions shown do not account for mounting gasket.

NOT UP-TO-DATE
www.docuthek.com

© Eclipse, Inc. All Rights Reserved