



Number: UKCA/0558/22/053 Replaces: 17GR0205/00

Issue Date: 04-02-2022 Contract Number: PS7133

**Due Date**: 04-02-2032 **Module**: B (Type Testing)

Report Number: 120408 Scope: Gas Appliances

PIN: 0063AU1408 Page 1 of 2

## **UKCA TYPE EXAMINATION CERTIFICATE**

Kiwa Ltd. hereby declares that the model type(s)

GFK...

Manufactured by Elster GmbH (Honeywell)

Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: BS EN 13611:2007+A2:2011

Signed on behalf of Kiwa Ltd. (UK Approved Body Number 0558)

m 1 Contre

Mark Crowther Technical Director

Kiwa Ltd.

Kiwa Gastec Kiwa House

Malvern View Business Park Stella Way Bishops Cleeve Cheltenham GL52 7DQ

United Kingdom T +44 (0)1242 677877 F +44 (0)1242 676506

www.kiwa.co.uk





0217



**Number:** UKCA/0558/22/053 **Replaces:** 17GR0205/00

Issue Date: 04-02-2022 Contract Number: PS7133

**Due Date:** 04-02-2032 **Module:** B (Type Testing)

**Report Number:** 120408 **Scope:** Gas Appliances

# APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

#### List of all available types:

Gas filter approved on relevant clauses of EN 13611.

#### Type Number Survey:

GFK	Gas Filter
15	Connection size 15
20	Connection size 20
25	Connection size 25
32	Connection size 32
40	Connection size 40
50	Connection size 50
65	Connection size 65
80	Connection size 80
100	Connection size 100
125	Connection size 125
150	Connection size 150
200	Connection size 200
250	Connection size 250
R F N A	Rp thread (connection size 15, 20, 25, 32, 40, 50, 65) DIN flanged (connection size 40, 50, 65, 80, 100, 125, 150, 200, 250) NPT thread (connection size 15, 20, 25, 32, 40, 50, 65) ANSI flanged (connection size 40, 50, 65, 80, 100)
Т	T product
10	pe max. = 1 bar
40	pe max. = 4 bar
60	pe max. = 6 bar
-3	Plug screw at the inlet and outlet
-6	Measuring adapter at the inlet and outlet

### Special conditions:

None