



Number:	UKCA/0558/21/306	Replaces:	17GR0190/00
Issue Date:	06-12-2021	Contract Number:	PS7133
Due Date:	06-12-2031	Module:	B (Type Testing)
Report Number:	121154	Scope:	Gas Appliances
PIN:	0063BM1154	Page	1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

BVA,
BVAF,
BVG,
BVGf

Manufactured by **Elster GmbH (Honeywell)**
Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: **BS EN 161:2011+A3:2013**

Signed on behalf of Kiwa Ltd.
(UK Approved Body Number 0558)

Mark Crowther
Technical Director
Kiwa Ltd.

39017601

CERTIFICATE

Kiwa Gastec
Kiwa House
Malvern View Business Park
Stella Way
Bishops Cleeve
Cheltenham
GL52 7DQ
United Kingdom
T +44 (0)1242 677877
F +44 (0)1242 676506
www.kiwa.co.uk



0217



Number:	UKCA/0558/21/306	Replaces:	17GR0190/00
Issue Date:	06-12-2021	Contract Number:	PS7133
Due Date:	06-12-2031	Module:	B (Type Testing)
Report Number:	121154	Scope:	Gas Appliances
PIN:	0063BM1154	Page	2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

The Elster GmbH butterfly-valve(s), Type BVG, are intended for use on gas burners, gas appliances and similar use.

List of all available types:

Ambient temperature range:	-20°C to +60°C
Working pressure:	Pe max = 500 mbar, delta Pmax = 150 mbar
Connection sizes:	40, 50, 65, 80, 100, 125, 150

Butterfly valve for gas	BVG
Butterfly valve for gas without hysteresis	BVGF
Butterfly valve for air	BVA
Butterfly valve for air without hysteresis	BVAF

Nominal size	40
	50
	65
	80
	100
	125
	150

Reduced nominal size	/25
	/50
	/65
	/80
	/100
	/125

For fitting between two DIN flanges	Z
For fitting between two ANS flanges	W

Pe max = 500 mbar (7.25 PSI)	05
------------------------------	----

With manual adjustment	H
With square shaft	V
With free shaft end	F
With attachment kit for E.C.B.	E

Special conditions:

None