



Number: UKCA/0558/21/308 Replaces: 18GR0580/00

Issue Date: 06-12-2021 Contract Number: PS7133

Due Date: 06-12-2031 **Module:** B (Type Testing)

Report Number: 124310 Scope: Gas Appliances

PIN: 0063BT1310 **Page** 1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

IFD 2xx

Manufactured by Elster GmbH (Honeywell)

Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: BS EN 298:2012, BS EN 14459:2007

Signed on behalf of Kiwa Ltd. (UK Approved Body Number 0558)

m 2 Contre

Mark Crowther Technical Director

Kiwa Ltd.

Kiwa Gastec Kiwa House

Malvern View Business Park Stella Way Bishops Cleeve Cheltenham GL52 7DQ United Kingdom

T +44 (0)1242 677877 **F** +44 (0)1242 676506

www.kiwa.co.uk





0217



Number: UKCA/0558/21/308 **Replaces:** 18GR0580/00

Issue Date: 06-12-2021 Contract Number: PS7133

Due Date: 06-12-2031 **Module:** B (Type Testing)

Report Number: 124310 Scope: Gas Appliances

PIN: 0063BT1310 **Page** 2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

Manufacturer: Elster GmbH (Honeywell)

<u>Types:</u> IFD 244-x /1 Q (I)

IFD 244-x /2 Q (I) IFD 244-x /1 W (I) (Z) IFD 244-x /2 W (I)

IFD 258-x /1 Q (I) IFD 258-x /2 Q (I) IFD 258-x /1 W (I) IFD 258-x /2 W (I)

IFD 258-x /1 Y (I) IFD 258-x /2 P (I)

x=3, 5 or 10 s.

Optional (I) integrated Ignition. Optional (Z) customized version.

Scope:

Application: Appliances burning gaseous and permanent operation (Ionisation)

Appliances burning gaseous and non-permanent operation (UV detector)

Flame detection: Ionisation, external UV detector UVS

Applied technology: Complex electronics
Ambient temperature: -20 °C to +60 °C

Electrical supply: (P)100 - (R)115 - (Q)120 - (Y)200 - (W)230 Vac 50/60Hz

Protection: With enclosure and IP 54
Installation environment Pollution degree 1, 2 or 3
Gas valve output: Urated may 1.0.4

Gas valve output: Urated.max. 1.0 A

See the installation and operating instructions for all specifications and possible options available for the above listed type(s).

Approved safety relevant functions:

Automatic burner control system: EN 298 Class C Reset function: EN 14459, Annex J Class B

Remarks/special conditions:

None.