

RABO Compact Configuration Sheet 03.01.2023

Customer: _____ PO Number: _____ Date: _____

Feature		Configuration (Standards are marked in bold)
Base Meter	Version	☐ Thread ☐ Flange
	Adapter	☐ Yes (only available for Thread version) ☐ No
	Meter size	☐ G10 ☐ G16 ☐ G25 ☐ G40 (on request)
	Meter diameter	☐ DN25 ☐ DN32 ☐ DN40 ☐ DN50
	Pressure class	☐ PN16 ☐ ANSI150
	Face-to-face length	☐ 121mm (Thread version) ☐ 171mm (Flange version)
Testing	Calibration / Testing	☐ MID ☐ works tested
	Language Certificate	☐ German ☐ English
	Measuring range	☐ 1:200 (on request) ☐ 1:160 ☐ 1:130 ☐ 1:100 ☐ 1:80 ☐ 1:65 ☐ 1:50 ☐ 1:30 ☐ 1:20
Installation	Flow direction	☐ Left ➡ Right ☐ Right ➡ Left ☐ Top ➡ Down ☐ Bottom ➡ Up
	Mounting of EVC	☐ No ☐ EK280 ☐ EK205
Counter	Totalizer Variant	☐ S1V ☐ S1D ☐ S1D with Encoder ☐ Other, please specify: _____
LF-Output	LF-pulse output	☐ none ☐ INS-10 ☐ INS-11 ☐ INS-12 ☐ Other, please specify: _____

RABO Compact Configuration Sheet 03.01.2023

Customer: _____ PO Number: _____ Date: _____

Feature		Configuration (Standards are marked in bold)
Accessories and Misc.	Oil free	☐ Yes ☐ No
	Oil sight glass	☐ Yes (not available for oil free) ☐ No
	HF-Pulse output A1K	☐ Yes ☐ No
	Thermowell	☐ 0 ☐ 1 ☐ 2
	Pressure tap	☐ none(plugged) ☐ Ermeto ☐ Swagelok
	Sealing of meter head	☐ adhesive seal ☐ seal wire
	Sealing oil screws	☐ No ☐ Yes
	Cone sieve	☐ 0 ☐ 1 ☐ 2

Project / Customer reference / Comments / Special requests

Customer, Address: _____

Contact person: _____

Tel.: _____ E-Mail: _____