

This product is discontinued!



EK260 – Product Configuration 11/2011

Customer: _____ Order number: _____ Date: _____

Feature		Configuration - Defaults are marked bold		
General	Destination/Country			
	Language in device	<input type="checkbox"/> English	<input type="checkbox"/> French <input type="checkbox"/> German <input type="checkbox"/> _____	
	Parameterisation	<input type="checkbox"/> Standard <input type="checkbox"/> According to customer specification		
	Owner number	<input type="checkbox"/> _____ Bar	code: <input type="checkbox"/> _____	
	Time base	<input type="checkbox"/> MEZ / CET (no summer time) <input type="checkbox"/> MESZ / CEST		
	Difference to time base	<input type="checkbox"/> _____ hours to UTC	Beginn of day: <input type="checkbox"/> 06:00 o'clock <input type="checkbox"/> _____ o'clock	
	Number of batteries	<input type="checkbox"/> 2 (Battery lifetime 5 years) <input type="checkbox"/> 4 (in Encoder mode) If the EK260 will supply by an external source (e.g. in combination with EM260 or FE260) 2 Batteries are sufficient		
Input	Encoder interface	<input type="checkbox"/> No <input type="checkbox"/> Yes		
	Pulse value (cp-Value); Omitted for encoder	<input type="checkbox"/> 1 Imp. / m³ <input type="checkbox"/> 0.1 Imp. / m ³ <input type="checkbox"/> 0.01 Imp. / m ³ <input type="checkbox"/> 10 Imp. / m ³ <input type="checkbox"/> 100 Imp. / m ³ <input type="checkbox"/> _____ Imp. / m ³		
VC	Compressibility	<input type="checkbox"/> fixed <input type="checkbox"/> AGA8 GC 1 <input type="checkbox"/> SGERG 88 <input type="checkbox"/> AGA8 GC 2 <input type="checkbox"/> AGA-NX19 <input type="checkbox"/> AGA-NX19 Hering & Wollowski		
	Calculation method			
Test	Calibration / Test	<input type="checkbox"/> MID → for all countries which belong to the European Union <input type="checkbox"/> factory checked → for all other countries <input type="checkbox"/> function checked → without calibration of the sensors		
Pressure sensor	Pressure sensor version	<input type="checkbox"/> internal <input type="checkbox"/> external (cable length 10m, cable T-sensor than also 10 m)		
	Pressure range	<input type="checkbox"/> 0.7 – 2.0 bar a <input type="checkbox"/> 2.4 – 12.0 bar a <input type="checkbox"/> 14.0 – 70.0 bar a <input type="checkbox"/> 0.8 – 5.0 bar a <input type="checkbox"/> 4.0 – 20.0 bar a <input type="checkbox"/> 16.0 – 80.0 bar a <input type="checkbox"/> 1.4 – 7.0 bar a <input type="checkbox"/> 6.0 – 30.0 bar a <input type="checkbox"/> 2.0 – 10.0 bar a <input type="checkbox"/> 8.0 – 40.0 bar a		
		Base Pressure	<input type="checkbox"/> 1.01325 bar <input type="checkbox"/> _____ <input type="checkbox"/> bar <input type="checkbox"/> psi <input type="checkbox"/> MPa	
		Pressure unit	<input type="checkbox"/> bar <input type="checkbox"/> psi <input type="checkbox"/> kPa <input type="checkbox"/> MPa	
Temp	T-Sensor cable length	<input type="checkbox"/> 2.5 m → 10 m in combination with an external pressure sensor		
	Temperature unit	<input type="checkbox"/> °C <input type="checkbox"/> °F		
	Base Temperature	<input type="checkbox"/> 273.15 K = 0°C <input type="checkbox"/> 288.15 K <input type="checkbox"/> 293.15 K <input type="checkbox"/> _____ K		
Installation	Housing Seals	<input type="checkbox"/> no <input type="checkbox"/> sealing screws		
	Mounting options	<input type="checkbox"/> wall mounting – without any brackets <input type="checkbox"/> Mounting plate IRM-1 <input type="checkbox"/> index head S1 (TRZ2 / RVG / Q steel) <input type="checkbox"/> Mounting plate IRM-3 <input type="checkbox"/> Mounting plate for Multi index or MI-2 (SM-RI-X / Q75)		
		Pulse input cable	<input type="checkbox"/> without cable Only for pulse mode: <input type="checkbox"/> 0.7m pulse cable INS-11/12 (for meter index type S1) <input type="checkbox"/> 2.7m pulse cable (with open ends) Only for encoder mode: <input type="checkbox"/> 0.7m cable <input type="checkbox"/> 2.7m cable	
	Already prepared to connect to an ELSTER accessory device		<input type="checkbox"/> no <input type="checkbox"/> EM260 mit... <input type="checkbox"/> FE260 mit... <input type="checkbox"/> FE230 <input type="checkbox"/> Analogmodem <input type="checkbox"/> GSM-Modem <input type="checkbox"/> ISDN-Modem <input type="checkbox"/> Ethernet <input type="checkbox"/> GPRS - TSC <input type="checkbox"/> GPRS - TCPServ <input type="checkbox"/> GPRS - ComFTP	

Project / Customer reference / Comments:

Customer, Address: _____

Contact person: _____ Phone: _____ E-Mail: _____

Please send the filled document together with your order to:
 Elster GmbH • Steinern Straße 19-21 • D-55252 Mainz-Kastel • Fax: +49 6134 / 605 - 390