



ECLIPSE BV-PAK

Packaged Butterfly Valve & Actuator



Simple, packaged convenience

Honeywell Eclipse makes selection and ordering easy with this single source flow control solution. A quick, simple configuration provides a ready to go “out of the box” product, offering fast, easy assembly and installation in your industrial and commercial combustion systems.

The Simple Support

Mounting and setup are all made easier with the BV-Pak v3. The new, innovative support provides a robust, universal solution that will not bend – a durable component ready for the vigorous demands of applications around the world. A position indicator provides feedback to the operator about valve settings.

Precision Meets the Industry Standard

For applications requiring modulating precision and repeatability, the Packaged Butterfly Valve is the ultimate solution. High step resolution, reliability and ample torque of the Kromschroder IC Series Actuator combines with the robust, world renowned Eclipse Butterfly Valve for ultimate burner and flow control.

Ready for the World

The Packaged Butterfly Valve is ready for installation anywhere in the world. The IC20 Actuator meets European standards. The IC40 Actuator meets USA, Canadian and European standards. The BV-Pak v3 is available in sizes from 1/2” to 4” with RC or NPT threads.

For More Information

The Honeywell Thermal Solutions family of products includes Honeywell Combustion Safety, Honeywell Combustion Service, Eclipse, Exothermics, Hauck, Kromschroder and Maxon. To learn more about our products, visit ThermalSolutions.honeywell.com or contact your Honeywell Sales Engineer.

Honeywell Thermal Solutions

Honeywell Thermal Solutions (HTS)
1250 West Sam Houston Parkway
South Houston, TX 77042
ThermalSolutions.honeywell.com



Actuator Options

Two actuator models are available : the IC20 and the IC40 actuator.

IC20 Actuator features:

- Available in 120VAC and 230VAC versions
- Standard model can be driven by 2 and 3 position step control, with optional 1000 Ohm feedback potentiometer
- Optional “Electronic” model can be driven by 0(4)-20 mA or 0-10VDC signal, with 4-20mA position feedback

IC40 Actuators features:

- 100-230 VAC mains voltage
- “Digital” models can be driven by 2, 3 and 4 position step control
- “Analog” models can be driven by 2, 3 and 4 position step control, or with 4-20 mA signal
- Optional 1000 Ohm feedback potentiometer available on both actuator models