

EC type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085BL0539

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Elster GmbH Strothweg 1, D-49504 Lotte (Büren)
Distributor <i>Vertreiber</i>	Elster GmbH Strothweg 1, D-49504 Lotte (Büren)
Product Category <i>Produktart</i>	gas fittings: Thermically triggered shut-off device (4340)
Product Description <i>Produktbezeichnung</i>	straight pattern thermically triggered shut-off valve (TAE) with metallic sealing disk
Model <i>Modell</i>	TAS 10/15/20/25 ...
Countries of Destination <i>Bestimmungsländer</i>	European Union, CH, IS, NO
Test Reports <i>Prüfberichte</i>	type testing: 17/336/4340/123 from 18.12.2017 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN 3586 (01.10.2003)

Validity / File no. 21.04.2018 until 26.01.2028 / 17-0962-GEA
Gültigkeit / AZ

26.01.2018 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EC Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.




DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases of the 1., 2. & 3. gas family	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
TAS 10...	nominal diameter: DN 10 max. operating pressure: 5 bar	
TAS 15...	nominal diameter: DN 15 max. operating pressure: 5 bar	
TAS 20...	nominal diameter: DN 20 max. operating pressure: 5 bar	
TAS 25...	nominal diameter: DN 25 max. operating pressure: 5 bar	

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

corrosion protection: zinc coating (standard valves) respectively nickel coating ("biogas valves" TAS ...BG)
connections: on the input side female thread Rp 1/2...Rp 1 according to DIN EN 10226-1;
on the output side: female thread Rp 1/2...Rp 1 or male thread R 1/2...R 1 according to DIN EN 10226-1 or optional TAS
..SG with special thread (metric male thread)
response temperature: 95 °C +/- 5 K
higher thermic chargeability: +650 °C
max. ambient temperature: +80 °C