

BURNER MODEL TriOx 3008

INVISIFLAME MODE⁵

NATURAL GAS, AMBIENT COMBUSTION AIR OPERATION

SPECIFICATIONS		OPERATIONAL INFORMATION			
Capacity (at 5% Excess Air)	(MMBTU/hr)	1.1	3.2	5.3	8.0
	(kW)	280	840	1,410	2,120
Air Capacity	(SCFH)	10,400	31,500	52,700	79,100
	(nm ³ /hr)	280	840	1,410	2,120
Air Pressure (Body)	(in.w.c.)	0.3	2.9	8.2	18.4
	(mbar)	0.8	7.2	20.3	45.7
Gas Inlet Pressure	(in.w.c.)	0.2	1.8	5.0	11.2
	(mbar)	0.5	4.4	12.3	27.8
Combustion Zone Length ⁴	(ft)	10.0	12.0	15.0	18.0
	(m)	3.0	3.7	4.6	5.5
Combustion Zone Diameter ⁴	(ft)	3.0	3.5	4.0	5.0
	(m)	0.9	1.1	1.2	1.5
Maximum Excess	(Air %)	500	750	1,000	1,500
	(Fuel %)	+30	+30	+30	+30

BURNER MODEL TriOx 4008

INVISIFLAME MODE⁵


NATURAL GAS, 900°F / 482°C COMBUSTION AIR OPERATION

SPECIFICATIONS		OPERATIONAL INFORMATION			
Capacity (at 5% Excess Air)	(MMBTU/hr)	0.6	2.0	3.3	5.1
	(kW)	170	520	870	1,360
Air Capacity	(SCFH)	6,400	19,400	32,500	50,600
	(nm ³ /hr)	170	520	870	1,360
Air Pressure (Body)	(in.w.c.)	0.3	2.9	8.1	19.8
	(mbar)	0.8	7.2	20.3	49.1
Gas Inlet Pressure	(in.w.c.)	0.1	1.0	2.9	6.9
	(mbar)	0.3	2.5	7.1	17.3
Combustion Zone Length ⁴	(ft)	8.0	10.0	12.0	15.0
	(m)	2.4	3.0	3.7	4.6
Combustion Zone Diameter ⁴	(ft)	2.5	3.0	3.5	4.0
	(m)	0.8	0.9	1.1	1.2
Maximum Excess	(Air %)	250	500	750	1,000
	(Fuel %)	+30	+30	+30	+30

- NOTES: 1. Capacities based on Natural Gas with HHV of 1034 BTU/ft³ (Standard), and LHV of 10.21 kWh/nm³ (Metric), 0.59 S.G., and a stoichiometric ratio of 9.74:1 with burner firing into chamber under no pressure at 5% excess air.
2. Air and fuel flows based on STP operating conditions at sea level and industry standard air and gas piping practices.
3. Flame detection is not possible on the 3000 and 4000 Invisiflame™ Mode only versions of the burner.
4. The combustion zone when operating Invisiflame™ Mode is not visible unless used with preheated combustion air.
5. Invisiflame™ Mode is suitable for furnace or chamber temperatures above 1600°F or 870°C only. For temperatures less than 1600°F or 870°C the TriOx burner must be used in Firing Mode only.


TriOx 3008 Burner Pressure Curves

InvisiFlame Mode, Ambient Combustion Air
Natural Gas 1034 BTU/scf (HHV), S.G. 0.59




TriOx 3008 Burner Pressure Curves

InvisiFlame Mode, Ambient Combustion Air
Natural Gas 10.21kWh/nm³ (LHV), S.G. 0.59



TriOx 4008 Burner Pressure Curves

InvisiFlame Mode, 900°F Combustion Air
Natural Gas 1034 BTU/scf (HHV), S.G. 0.59



TriOx 4008 Burner Pressure Curves

InvisiFlame Mode, 482°C Combustion Air
Natural Gas 10.21kWh/nm³ (LHV), S.G. 0.59

