

## EK220 – Product Configuration

11.12.2020

Customer: \_\_\_\_\_ Order number: \_\_\_\_\_ Date: \_\_\_\_\_

Feature		Configuration (Defaults are marked in bold)	
Basic device	Customer specification	<input type="checkbox"/> <b>standard</b>	<input type="checkbox"/> customer specification acc. _____
	Destination/country	<input type="checkbox"/> <b>EU</b>	<input type="checkbox"/> Germany <input type="checkbox"/> _____
	Language used in device	<input type="checkbox"/> <b>English</b>	<input type="checkbox"/> German <input type="checkbox"/> French
	Parametrization	<input type="checkbox"/> <b>standard</b>	<input type="checkbox"/> according to customer spec. (customer release)
	Compressibility	<input type="checkbox"/> <b>S-GERG-88</b>	<input type="checkbox"/> AGA-NX19 <input type="checkbox"/> AGA8 GC 1
	Calculation method (K value mode)	<input type="checkbox"/> AGA8 GC 2 <input type="checkbox"/> AGA8-92DC	<input type="checkbox"/> AGA-NX19 Hering & Wollowski <input type="checkbox"/> fixed value
	Difference to time base	<input type="checkbox"/> _____ hours to UTC (GMT)	
	Calibration / Test	<input type="checkbox"/> <b>MID</b> → for all countries which belong to the EU <input type="checkbox"/> factory checked → for all other countries	
	Type of Ex approval	<input type="checkbox"/> <b>ATEX approval</b> <input type="checkbox"/> according to IEC Ex approval	
	Housing option	<input type="checkbox"/> <b>standard housing (IP65)</b> <input type="checkbox"/> enhanced outdoor housing	
	Housing seals	<input type="checkbox"/> <b>standard</b> <input type="checkbox"/> Sealing screws	
Pressure sensor	Pressure sensor type	<input type="checkbox"/> <b>CT30 internal</b> <input type="checkbox"/> CT30 external cable length 10m also for T-sensor	<input type="checkbox"/> 17002 external cable length 2,7 m
	Pressure ranges (absolute)	<input type="checkbox"/> 0.7 – 2.0 bar a <input type="checkbox"/> <b>0.8 – 5.0 bar a</b> <input type="checkbox"/> 2.0 – 10.0 bar a <input type="checkbox"/> 4.0 – 20.0 bar a <input type="checkbox"/> 8.0 – 40.0 bar a <input type="checkbox"/> 14.0 – 70.0 bar a <input type="checkbox"/> 16.0 – 80.0 bar a other pressure ranges available on request	<input type="checkbox"/> 0.9 – 7.0 bar a <input type="checkbox"/> 0.9 – 10.0 bar a
	Base Pressure	<input type="checkbox"/> <b>1.01325 bar</b> <input type="checkbox"/> _____	
	Unit for pressure	<input type="checkbox"/> <b>bar</b> <input type="checkbox"/> psi <input type="checkbox"/> kPa <input type="checkbox"/> MPa	
T-Sensor	T-Sensor cable length	<input type="checkbox"/> <b>2.5 m</b> <input type="checkbox"/> 10 m	
	Unit for temperature	<input type="checkbox"/> <b>°C</b> <input type="checkbox"/> °F	
	Base Temperature	<input type="checkbox"/> <b>273.15 K = 0°C</b> <input type="checkbox"/> 288.15 K <input type="checkbox"/> 293.15 K <input type="checkbox"/> _____ K	
Options	Mounting options	<input type="checkbox"/> <b>wall mounted</b> <input type="checkbox"/> index head S1/M-2 (w/o mounting the meter in the factory) <input type="checkbox"/> index head S1/M-2 ( <u>with</u> mounting the meter in the factory) requires also the meter which must be part of the order!	
	Pulse input cable	<input type="checkbox"/> <b>without cable</b> <input type="checkbox"/> 0.7m cable with socket for INS11/12 pulser <input type="checkbox"/> 2.7m cable with open wires <input type="checkbox"/> 2.7m cable with INS10 pulser <input type="checkbox"/> 0.7m cable with INS10 pulser	
	Number of batteries	<input type="checkbox"/> <b>1 battery</b> <input type="checkbox"/> 2 batteries	
	Cp value input 1	_____	
	Barcode	<input type="checkbox"/> <b>no</b> <input type="checkbox"/> yes, type: _____	
	Owners label	<input type="checkbox"/> <b>no</b> <input type="checkbox"/> yes, acc. to customer spec; type: _____	
	Certification Data Log	<input type="checkbox"/> <b>active</b> (change of specified values - e.g. input mode, cp value, meter reading, etc. - possible without breaking the calibration seal) <input type="checkbox"/> inactive (change of specified values only possible by open calibration lock)	

Please send the filled document together with your order to:

Page 1 / 2

Honeywell | Process Solutions • Steinern Straße 19-21 • D-55252 Mainz-Kastel

• Fax: +49 6134 / 605 – 390 • E-Mail: [gas-mainz-orders@honeywell.com](mailto:gas-mainz-orders@honeywell.com)

*Default options are marked in bold; please mark the desired options!*

**Project / Customer reference / Comments:**

---

---

---

Customer Address: \_\_\_\_\_

---

Contact person: \_\_\_\_\_

Phone: \_\_\_\_\_ E-Mail: \_\_\_\_\_