



Number:	UKCA/0558/22/055	Replaces:	17GR0210/00
Issue Date:	04-02-2022	Contract Number:	PS7133
Due Date:	04-02-3032	Module:	B (Type Testing)
Report Number:	119262	Scope:	Gas Appliances
PIN:	0063BQ001/04	Page	1 of 2

## UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

S11T

Manufactured by **Elster GmbH (Honeywell)**  
Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

**Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.**

Reference standards: BS EN 125:2010

Signed on behalf of Kiwa Ltd.  
(UK Approved Body Number 0558)

Mark Crowther  
Technical Director  
Kiwa Ltd.

39017601

# CERTIFICATE

**Kiwa Gastec**  
Kiwa House  
Malvern View Business Park  
Stella Way  
Bishops Cleeve  
Cheltenham  
GL52 7DQ  
United Kingdom  
T +44 (0)1242 677877  
F +44 (0)1242 676506  
[www.kiwa.co.uk](http://www.kiwa.co.uk)



0217



<b>Number:</b>	UKCA/0558/22/055	<b>Replaces:</b>	17GR0210/00
<b>Issue Date:</b>	04-02-2022	<b>Contract Number:</b>	PS7133
<b>Due Date:</b>	04-02-2032	<b>Module:</b>	B (Type Testing)
<b>Report Number:</b>	119262	<b>Scope:</b>	Gas Appliances
<b>PIN:</b>	0063BQ001/04	<b>Page</b>	2 of 2

## APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

### List of all available types:

Thermo-electric flame supervision devices approved on EN125

Class A

Mechanical strength                      Group 2

Max. ambient temperature                -20°C / 60°C

### TYPE NUMBER SURVEY:

S11T                      Thermo-electric valve type S11T

15                      Connection size DN 15

20                      Connection size DN 20

25                      Connection size DN 25

R                      Screw connections acc. ISO 7-1

01                      Maximum inlet pressure 100 mbar

15                      Maximum inlet pressure 1,5 bar

S                      optional switch

### Remark:

When the thermo-electrical valve is not provided with the optional switch, the letter 'S' is not listed in the type number survey