

# HONEYWELL ELSTER MR PN 10



Maximum Capacity Table

## MR 25 PN 10

Outlet pressure (mbar)	Accuracy class	Inlet pressure [mbar]						
		100	500	1,000	3,000	5,000	7,000	10,000
22	AC10	21	46	77	143	184	261	358
50	AC10	23	63	94	184	252	325	426
100	AC10	-	48	88	187	305	393	494
300	AC10	-	36	65	171	253	363	496
500	AC10	-	-	82	224	344	463	657

m<sup>3</sup>/hr

## MR 50 PN 10

Outlet pressure (mbar)	Accuracy class	Inlet pressure [mbar]						
		100	500	1,000	3,000	5,000	7,000	10,000
22	AC10	100	204	266	470	797	1022	
50	AC10	52	126	189	409	756	1049	
100	AC10	-	177	264	560	835	994	
300	AC10	-	97	168	428	726	985	
500	AC10	-	-	257	717	1075	1434	
100	AC5	-	110	154	352	637	824	1187
300	AC5	-	52	104	246	389	648	907
500	AC5	-	-	149	358	657	896	1270

m<sup>3</sup>/h

### Your contacts

[www.smartenergy.honeywell.com](http://www.smartenergy.honeywell.com)

### Honeywell | Smart Energy

Germany  
Elster GmbH  
Steinern St. 19 – 21  
55252 Mainz -Kastel  
T +49 6134 605 0  
[gas-mainz-se@honeywell.com](mailto:gas-mainz-se@honeywell.com)