



Number: UKCA/0558/21/305 Replaces: 17GR0209/00

Issue Date: 06-12-2021 Contract Number: PS7133

Due Date: 06-12-2031 Module: B (Type Testing)

Report Number: 120909 Scope: Gas Appliances

PIN: 0063BL1554 **Page** 1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

VGP

Manufactured by Elster GmbH (Honeywell)

Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: BS EN 161:2011+A3:2013

Signed on behalf of Kiwa Ltd. (UK Approved Body Number 0558)

M 1 Contre

Mark Crowther Technical Director

Kiwa Ltd.

Kiwa Gastec Kiwa House

Malvern View Business Park Stella Way Bishops Cleeve Cheltenham GL52 7DQ

T +44 (0)1242 677877 **F** +44 (0)1242 676506

www.kiwa.co.uk

United Kingdom





0217



Number: UKCA/0558/21/305 **Replaces:** 17GR0209/00

Issue Date: 06-12-2021 Contract Number: PS7133

Due Date: 06-12-2031 Module: B (Type Testing)

Report Number: 120909 Scope: Gas Appliances

PIN: 0063BL1554 **Page** 2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

List of available types:

VGP

Electro-magnetic automatic shut-off valve approved on EN 161 Class A.

Degree of protection : IP 54

Ambient temperature range : -20 to +60 \square C. Mechanical strength : group 2

Type number survey:

VGP 10...25 Connection size DN10, 25, 20 and 25

R Screw connections acc. ISO 7

01 Max. inlet pressure 150 mbar 02 Max. inlet pressure 200 mbar

W 230V, 50/60 Hz M 110V, 50/60 Hz Q 120V, 50/60 Hz

5 Electrical connection Rectifier adapter without DIN plug (DIN43650, ISO4400)

6 Electrical connection Rectifier adapter with DIN plug (DIN43650, ISO4400)
6L Electrical connection Rectifier adapter with DIN plug (DIN43650, ISO4400)

with signal lamp

7 Electrical connection Device socket, 3-pin, with rectifier circuit

V Viton valve disk seal

Z Customer specified control

Special conditions:

None