

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085CT0263

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Elster GmbH Strotheweg 1, D-49504 Lotte
Distributor <i>Vertreiber</i>	Elster GmbH Strotheweg 1, D-49504 Lotte
Product Category <i>Produktart</i>	accessories for gas appliances/pressure equipment: Automatic function control (4126)
Product Description <i>Produktbezeichnung</i>	Automatic function control optional with automatic shut-off valve
Model <i>Modell</i>	RV.../RVS...
Countries of Destination <i>Bestimmungsländer</i>	European Union, CH, IS, NO
Test Reports <i>Prüfberichte</i>	type testing: 15/153/4104/123 from 09.05.2018 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 126 (01.06.2012) DIN EN 161 (01.04.2013)

Date of Expiry / File No. 24.07.2028 / 18-0292-GEE
Ablaufdatum / AZ

24.07.2018 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Elektrical Data	120 V AC, 50/60 Hz, IP54
Elektrische Daten	230 V AC, 50/60 Hz, IP54
	24 V DC, IP54

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
RV.../RVS...	nominal diameter: DN 32	
RV.../RVS...	nominal diameter: DN 40	
RV.../RVS...	nominal diameter: DN 50	
RV.../RVS...	nominal diameter: DN 65	
RV...	nominal diameter: DN 80	
RV...	nominal diameter: DN 100	

Type Variation Ausführungsvariante	Explanations Erläuterungen
RV...	without automatic shut-off valve
RVS...	with integrated automatic shut-off valve

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

Maximum inlet pressure: 150/200/300/500/1000 mbar depending of type
Connections: flanges (DN 40 up to DN 100) or Moduline system with female thread (DN 32 up to DN 50)
Ambient temperature range: -20...+60 °C (NBR) or 0...+60 °C (Viton)
Mounting position: RV any, RVS vertical or horizontal (drive up)