



Number:	UKCA/0558/21/303	Replaces:	17GR0206/00
Issue Date:	06-12-2021	Contract Number:	PS7133
Due Date:	06-12-2031	Module:	B (Type Testing)
Report Number:	121463	Scope:	Gas Appliances
PIN:	0063BL1553	Page	1 of 2

UKCA TYPE EXAMINATION CERTIFICATE

Kiwa Ltd. hereby declares that the model type(s)

VG 6 - 15

Manufactured by **Elster GmbH (Honeywell)**
Lotte - Büren, Germany

Meet(s) the essential requirements as described in the:

Gas Appliances Regulation (Regulation (EU) 2016/426 as brought into GB law and amended), and the Gas Appliances (Enforcement) and Miscellaneous Amendment Regulations 2018 No 389, and amendments to UK SI 2019/696 Product Safety and Metrology, and subsequent amendments, The Product Safety, Metrology and Mutual Recognition Agreement (Amendment) (EU Exit) Regulations 2019 No 1246, and subsequent amendments. This certificate is not valid in Northern Ireland – and is applicable to England, Scotland and Wales only.

Reference standards: **BS EN 161:2011+A3:2013**

Signed on behalf of Kiwa Ltd.
(UK Approved Body Number 0558)

Mark Crowther
Technical Director
Kiwa Ltd.

39017601

CERTIFICATE

Kiwa Gastec
Kiwa House
Malvern View Business Park
Stella Way
Bishops Cleeve
Cheltenham
GL52 7DQ
United Kingdom
T +44 (0)1242 677877
F +44 (0)1242 676506
www.kiwa.co.uk

UK CA



0217



Number:	UKCA/0558/21/303	Replaces:	17GR0206/00
Issue Date:	06-12-2021	Contract Number:	PS7133
Due Date:	06-12-2031	Module:	B (Type Testing)
Report Number:	121463	Scope:	Gas Appliances
PIN:	0063BL1553	Page	2 of 2

APPENDIX TO UKCA TYPE EXAMINATION CERTIFICATE

List of available types:

VG: Electro-magnetic shut-off valve approved on EN 161

Electrical supply: 220/240 Vac, 120 Vac, 24 Vdc
IP Protection class: IP54
Class: A
Mechanical strength: group 2
Working pressure: Up to 1,8 bar
Connection size: Rp internal thread DN 6, 8, 10, 15/10

Type Survey:

VG Gas solenoid valve

6, 8, 10, 15/10 Nominal diameter

K Double-cone olive for 8 mm tube loosely enclosed
R Rp internal thread

01 Pu max. 100 mbar
02 Pu max. 360 mbar
04 Pu max. 500 mbar
18 Pu max. 1,8 bar

T mains voltage: 220/240 Vac, 50/60 Hz
Q mains voltage: 120 Vac, 50/60 Hz
K mains voltage: 24 Vdc

5 connection via standard plug without socket
6 connection via standard plug and socket
6L connection via standard plug and socket with lamp

G Low-noise

V Viton valve disc seal