

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L000899-4
Report Reference MH64447-19700825
Date 15-Apr-2021

Issued to: Honeywell PMT
Honeywell Process Solutions
6801 Sandburg Rd Golden Valley, MN
United States 55427

This is to certify that representative samples of YIOZ - Valves, Electrically Operated
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 429, Fifth Edition (Revised December 12, 2008)

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L000899-4
Report Reference MH64447-19700825
Date 15-Apr-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
V4055, followed by -A, -B, -D, -E, -F or -G, followed by four digits actuator with a Type V5055, followed by A, B, C, D or E, followed by four digits valve-body.	Safety valves
V4062A, actuator with Type V5055, followed by A, B, C or E valve-body.	Safety valves
V4062A or V4062D, actuator with Type V5097, followed by A, B, C, D or E, followed by four-digits valve-body with P/N 32002512 or 32002513 normally-open vent valve.	Safety valves
V4062D, actuator with Type V5055, followed by A, B, C or E valve-body.	Safety valves
V45055, followed by A, B, D, E, F or G, followed by four digits actuator with Type V5097, followed by A, B, C, D or E, followed by four digits valve-body with P/N 32002512 or 32002513 normally-open vent valve.	Safety valves
V5055A+	Safety valves
V5055B+	Safety valves
V5055C+	Safety valves
V5055D+	Safety valves
V5055E+	Safety valves
V9055A, actuator with Type V5097, followed by A, B, C or E valve-body with P/N 32002512 or 32002513 normally-open vent valve.	Safety valves
V9055A or V9055D, actuator with Type V5055, followed by A, B, C or E valve-body.	Safety valves
V9055D, actuator with Type V5097, followed by A, B, C or E valve-body with P/N 32002512 or 32002513 normally-open vent valve.	Safety valves



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

