



Number	17GR0207/02	Replaces	17GR0207/01
Issue date	01-03-2024	Contract number	E0001
Due date	01-03-2034	Module	B (Type testing)
Report number	119418	Scope	(EU) 2016/426 (9 March 2016)
PIN	0063BL1553		

EU TYPE EXAMINATION CERTIFICATE (GAR)

Kiwa hereby declares that the automatic shut-off valve, model(s):

VG

Manufacturer

Elster GmbH (Honeywell) Strotheweg 1 49504 Lotte - Büren Germany

meet(s) the essential requirements as described in the **Regulation (EU) 2016/426 relating to appliances burning gaseous fuels.**

Reference standard: EN 161: 2022

This certificate is only valid in combination with the appendix to this certificate, where specific information and/or conditions are given.

Ron Scheepers Managing director

Kiwa Nederland B.V. Wilmersdorf 50 P.O. Box 137 7300 AC APELDOORN The Netherlands

https://www.kiwaenergy.com



\sum

Number	17GR0207/02	Replaces	17GR0207/01
Issue date	01-03-2024	Contract number	E0001
Due date	01-03-2034	Module	B (Type testing)
Report number	119418	Scope	(EU) 2016/426 (9 March 2016)
PIN	0063BL1553	Page	1 of 1

APPENDIX TO EU TYPE EXAMINATION CERTIFICATE (GAR)

<u>Manufacturer:</u>	
Elster GmbH (Honeywell)	

>

List of all available types:

VG: Electro-magnetic automatic shut-off valve approved on EN161

Electrical supply:	220/240 VAC, 120VAC; 24VDC
Ambient temperature range:	-20°C to 60°C
IP Protection degree:	IP54
Class:	A
Mechanical strength:	group 2
Working pressure:	up to 360 mbar
Connection size:	Rp internal thread DN 15, 20, 25, 32, 40 (ISO7)
Type survey	DIN Flange DN 32, 40, 50, 65 (ISO7005)
VG	Gas solenoid valve
10/15 - 65	Nominal diameter
R	Rp internal thread ISO7
F	Flange to ISO 7005
02	p. max. 200 mbar
03	p. max. 360 mbar
L	Slow opening, quick closing
N	Quick opening, quick closing
T	Mains voltage 220/240V AC, 50/60Hz
Q	Mains voltage 120V AC, 50/60Hz
K	Mains voltage 24 V DC
3	Terminal connection box IP54
6	Electrical connection with socket 6L
6L	Electrical connection with socket incl. lamp
1	Screw plug at the inlet
3	Screw plug at the outlet
D	With flow adjuster
M	Suitable for biologically produced methane
V	Viton valve disc seal
Z	With rolling diaphragm