CERTIFICATE OF COMPLIANCE

Certificate Number	UL-US-L000780
Report Reference	MP1436-19670420
Date	30-Aug-2019
Issued to:	MAXON CORP 201 E 18TH ST MUNCIE, IN United States 47302-4124
This is to certify that representative samples of	YIOZ - Valves, Electrically Operated See Addendum Page for Product Designation(s). Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.
Standard(s) for Safety:	UL 429 - 5th Ed - Issued 23 Mar 1999 - Revised 12 Dec 2008
Additional Information:	See the UL Online Certifications Directory at https://iq.ulprospector.com for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L000780
Report Reference MP1436-19670420
Date 30-Aug-2019

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
100 Series, 100, followed by 730, 760, 4730 or 4760, followed A or B, followed by 1 or 2.	Safety valve
125 Series, 125, followed by 730, 760, 4730 or 4760, followed A or B, followed by 1 or 2.	Safety valve
250CMA1, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, or D, followed by 1 or 2, followed by 0, 1, 2, or 3, followed A, followed by 0.	Safety valves
300CMA1, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, or D, followed by 1 or 2, followed by 0, 1, 2, or 3, followed A, followed by 0.	Safety valves
400CMA1, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, or D, followed by 1 or 2, followed by 0, 1, 2, or 3, followed A, followed by 0.	Safety valves
250CMM1, followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, D, or E, followed by 0, 1, 2, or 3, followed A, followed by 0.	Safety valves
400CMM2, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, followed by 0, 1, 2 or 3, followed A, followed by 0.	General purpose valves
300CMM2, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, followed by 0, 1, 2 or 3, followed A, followed by 0.	General purpose valves
250CMM2, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, followed by 0, 1, 2 or 3, followed A, followed by 0.	General purpose valves
400CMA2, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A,	General purpose valves

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L000780
Report Reference MP1436-19670420
Date 30-Aug-2019

B, C, or D, followed by 1 or 2, followed by 0, 1, 2, or 3, followed A, followed by 0.	
300CMA2, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, or D, followed by 1 or 2, followed by 0, 1, 2, or 3, followed A, followed by 0.	General purpose valves
250CMA2, , followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, or D, followed by 1 or 2, followed by 0, 1, 2, or 3, followed A, followed by 0.	General purpose valves
400CMM1, followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, D, or E, followed by 0, 1, 2, or 3, followed A, followed by 0.	Safety valves
300CMM1, followed by 1, followed by A or B, followed by A, B, C, E, or F, followed by 1, 2, 5, or 6, followed by 1 or 2, followed by A, B, C, D, E, F, or G, followed by A, B, C, D, or E, followed by 0, 1, 2, or 3, followed A, followed by 0.	Safety valves

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/